

Thyristor Surge Protective Device

Part Number	RA0640L	RA0720L	RA0900L	RA1100L	RA1300L	RA1500L	RA1800L	RA2300L	RA2600L	RA3100L	RA3500L	RA4000L	Breakover Current (I _{Bo})		Holding Current (I _H)		Package
	Rated Repetitive Off-State Voltage (V _{DRM}) Max (V)	58	65	75	90	120	140	170	190	220	275	320	360	Min (mA)	Max (mA)	Min (mA)	
Breakover Voltage (V _{Bo}) Max (V)	77	88	98	130	160	180	220	265	300	350	400	450	50	800	150	800	SMA
Off-State Leakage Current @VDRM (IDRM) Max (uA)		5		On-State Voltage @IT=1A (VT) Max. (V)		3.5		Non-repetitive peak impulse current @10/1000us (IPP) (A)		50		Non-repetitive peak On-state current @8.3ms (one-half cycle) (ITSM) (A)		15			

Part Number	RB0640L	RB0720L	RB0900L	RB1100L	RB1300L	RB1500L	RB1800L	RB2300L	RB2600L	RB3100L	RB3500L	RB4000L	Breakover Current (I _{Bo})		Holding Current (I _H)		Package
	Rated Repetitive Off-State Voltage (V _{DRM}) Max (V)	58	65	75	90	120	140	170	190	220	275	320	360	Min (mA)	Max (mA)	Min (mA)	
Breakover Voltage (V _{Bo}) Max (V)	77	88	98	130	160	180	220	265	300	350	400	450	50	800	150	800	SMB
Off-State Leakage Current @VDRM (IDRM) Max (uA)		5		On-State Voltage @IT=1A (VT) Max. (V)		3.5		Non-repetitive peak impulse current @10/1000us (IPP) (A)		50		Non-repetitive peak On-state current @8.3ms (one-half cycle) (ITSM) (A)		15			

Thyristor Surge Protective Device

Part Number	RB0640M	RB0720M	RB0900M	RB1100M	RB1300M	RB1500M	RB1800M	RB2300M	RB2600M	RB3100M	RB3500M	RB4000M	Breakover Current (I _{Bo})		Holding Current (I _H)		Package
	Rated Repetitive Off-State Voltage (V _{DRM}) Max (V)	58	65	75	90	120	140	170	190	220	275	320	360	Min (mA)	Max (mA)	Min (mA)	
Breakover Voltage (V _{Bo}) Max (V)	77	88	98	130	160	180	220	265	300	350	400	450	50	800	150	800	SMB
	Off-State Leakage Current @VDRM (IDRM) Max (uA)		5	On-State Voltage @IT=1A (VT) Max. (V)		3.5	Non-repetitive peak impulse current @10/1000us (IPP) (A)		50	Non-repetitive peak On-state current @8.3ms (one-half cycle) (ITSM) (A)		30					

Part Number	RB0640H	RB0720H	RB0900H	RB1100H	RB1300H	RB1500H	RB1800H	RB2300H	RB2600H	RB3100H	RB3500H	RB4000H	Breakover Current (I _{Bo})		Holding Current (I _H)		Package
	Rated Repetitive Off-State Voltage (V _{DRM}) Max (V)	58	65	75	90	120	140	170	190	220	275	320	360	Min (mA)	Max (mA)	Min (mA)	
Breakover Voltage (V _{Bo}) Max (V)	77	88	98	130	160	180	220	265	300	350	400	450	50	800	150	800	SMB
	Off-State Leakage Current @VDRM (IDRM) Max (uA)		5	On-State Voltage @IT=1A (VT) Max. (V)		3.5	Non-repetitive peak impulse current @10/1000us (IPP) (A)		100	Non-repetitive peak On-state current @8.3ms (one-half cycle) (ITSM) (A)		50					